

KPC133

IR Dome Camera

Overview

1/3" AVTECH color CCD image sensor, Satisfied minimum illumination: 0.4 Lux / F2.0, 0Lux (IR ON), IR distance up to 15 meters with 21 IR LEDs.

Features

- High sensitivity in the dark environment, 0.4Lux / F2.0, 0Lux (IR ON)
- Day and night features for 24-hour surveillance
- Excellent image quality
- IR LED effective range reaches up to 15 meters



Specification

MODEL	KPC133
Pick up Element	1/3" AVTECH color CCD image sensor
Number of Pixels	512(H) x 492(V) <NTSC> / 512(H) x 582(V) <PAL>
Resolution	420TV lines
Min. Illumination	0 Lux (IR LED ON)
Effective IR Range	15 Meters
IR LED	21 units
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60(1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6°
IRIS Mode	AES
White Balance	ATW
Video Output	1.0 Vp-p composite, 75Ω
Power Source	DC12V±10%
Current Consumption	90mA (IR OFF), 280mA (IR ON)±10%

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm